

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2624631	elevat\$4 level\$3	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:25
L2	385098	leg	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:25
L3	23222	1 with 2	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:26
L4	1140616	screw\$2 thread\$2	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:27
L5	12807	3 not 4	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:28
L6	2284820	twist\$3 rotat\$3 pivot\$3	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:28
L7	6549	5 and 6	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:29
L8	3547475	slot groove (elongated (hole bore opening))	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:29
L9	567018	6 with 8	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:29
L10	2109	5 and 9	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:32
L11	2233	6 with 3	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:33
L12	161	(11 with 8) not 4	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:35
L13	5757	((248/188.2,188.4,188.5,188.7,188.8,188.9,407,649) or (16/32) or (5/11)).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO	OR	OFF	2004/11/24 13:35
L14	159	12 not 13	US-PGPUB; USPAT; EPO; JPO	OR	ON	2004/11/24 13:35